



Art.-Nr. / Item No.	Beschreibung / Description	Länge / Length (L)	Kabeltyp / Cable type	Farbe / color
50076	NK 101 G-200 2m grau	2000 ± 40 mm	H05VV-F 3G 0.75 mm ²	grau / grey
95288	NK 101 O-200 2m orange	2000 ± 40 mm	H05VV-F 3G 0.75 mm ²	orange / orange
95289	NK 101 O-300 3m orange	3000 ± 60 mm	H05VV-F 3G 1.00 mm ²	
95290	NK 101 O-500 5m orange	5000 ± 100 mm	H05VV-F 3G 1.00 mm ²	
68604	NK 101 S-150 1.5m schwarz	1500 ± 30 mm	H05VV-F 3G 0.75 mm ²	schwarz / black
50077	NK 101 S-200 2m schwarz	2000 ± 40 mm	H05VV-F 3G 0.75 mm ²	
50078	NK 101 S-250 2.5m schwarz	2500 ± 50 mm	H05VV-F 3G 1.00 mm ²	
95142	NK 101 S-300 3m schwarz	3000 ± 60 mm	H05VV-F 3G 1.00 mm ²	
51320	NK 101 S-500 5m schwarz	5000 ± 100 mm	H05VV-F 3G 1.00 mm ²	weiß / white
96030	NK 101 W-150 1.5m weiss	1500 ± 30 mm	H05VV-F 3G 0.75 mm ²	
95140	NK 101 W-200 2m weiss	2000 ± 40 mm	H05VV-F 3G 0.75 mm ²	
96031	NK 101 W-250 2.5m weiss	2500 ± 50 mm	H05VV-F 3G 1.00 mm ²	
95141	NK 101 W-300 3m weiss	3000 ± 60 mm	H05VV-F 3G 1.00 mm ²	
51321	NK 101 W-500 5m weiss	5000 ± 100 mm	H05VV-F 3G 1.00 mm ²	

Kaltgeräte Anschlusskabel, abgewinkelt

- universell einsetzbar
- geeignet für Kaltgeräte wie z.B. PC, Monitor, Beamer u.v.m.
- Anschlüsse: Schutzkontaktstecker (Typ F, CEE 7/7; S03), Gerätebuchse C13 (Kaltgeräteanschluss; ST3)
- Nennspannung: 250 V ~
- Nennstrom: 10/16 A
- Kabelspezifikation: H05VV-F 3G
- Konformität: RoHS

Cold-device connection cord, angled

- universally applicable
- suitable for cold devices such as PCs, monitors, beamers, etc.
- Connectors: Safety plug (type F, CEE 7/7; S03), Device socket C13 (IEC connection; ST3)
- Nominal voltage: 250 V ~
- Nominal current: 10/16 A
- Cable specifications: H05VV-F 3G
- Conformity: RoHS

Änderungen

Datum	Name	gez.:	Datum	Name
		gez.:	16.02.2021	aw
		gepr.:	16.02.2021	aw
		Norm:		
Änderungen vorbehalten / Subject to change				

Bezeichnung		Blatt
NK 101		1/1
Zeichnungs-Nr.:		von